

Whitewater Appliances

Model Specifications

Model	Virtual WWV110				WWA510				WWA710				WWA2010			
Configuration	L	M	H	VH	L	M	H	VH	L	M	H	VH	L	M	H	VH
Raw Disk Cache Capacity	N/A				3.5TB				7TB				11TB			
Useable Disk Cache Capacity	Up to 2TB				2TB				4TB				8TB			
Licensed Cloud Capacity ^(a)	1TB	2TB	4TB	8TB	4TB	6TB	8TB	10TB	8TB	10TB	15TB	20TB	16TB	20TB	30TB	40TB
RAID Protection level ^c	Customer provisioned ^(b)								RAID-6 ^(c)							
Network integration	2 x 1GbE								4 x 1GbE							
Maximum LAN throughput, aggregate (GB/Hr ^d)	250				400				600				1000			

(a) Base-10 capacity (i.e. TB – 1,000,000,000,000 bytes)- for WWA510/710/2010 appliances.

(b) Any customer provisioned RAID level that is valid and supported by VMWare ESXi 4.x

(c) Local storage with the Whitewater appliance only. (Excludes cloud storage).

(d) Max LAN throughput can be expected upto the amount listed

Physical Specifications

Model	WWA510				WWA710				WWA2010			
Configuration	L	M	H	VH	L	M	H	VH	L	M	H	VH
Profile					3U							
Memory	8GB				12GB				32GB			
Front Swappable Drives ⁽ⁱ⁾	7x500GB				7x1TB				11x1TB			
Onboard Ports (Copper)					6							
Dual Power Supplies					Yes							
Power [Watts] (Typical)	405				425				530			
BTU	1380				1450				1805			
Temperature					10 - 40 deg C / 50 - 95 deg F (Operating) / -40 - 65 deg C / -40 - 149 deg F (Storage)							
Relative Humidity ⁽ⁱⁱ⁾					20% - 80% non-condensing (Operating) / 5% - 95% non-condensing (Storage)							
Operating Acoustic noise					61 dBA Sound Pressure (Typical)							
System Dimensions (LxWxH) ⁽ⁱⁱⁱ⁾					25.72x17.0x5.2 in / 653.4x431.6x131.9 mm							
Packaging Dimensions					34.1x23.7x15.9 in / 866x602x403 mm							
Max Weight (without packaging)					65 Lbs / 29.5 Kg				71 Lbs / 32.3 Kg			
Rail information					Mounting rail kit included. Orderable spare part RMK-003							

(i) Hot swappable disks

(ii) Operating altitude up to 10,000 feet

(iii) Length is without bezel

The availability, export or re-export of these products or specific features are subject to the export laws and regulations of the U.S. and the laws and regulations of any applicable foreign agency or authority.



About Riverbed

Riverbed delivers performance for the globally connected enterprise. With Riverbed, enterprises can successfully and intelligently implement strategic initiatives such as virtualization, consolidation, cloud computing, and disaster recovery without fear of compromising performance. By giving enterprises the platform they need to understand, optimize and consolidate their IT, Riverbed helps enterprises to build a fast, fluid and dynamic IT architecture that aligns with the business needs of the organization. Additional information about Riverbed (NASDAQ: RVBD) is available at www.riverbed.com.



2005, 2006, 2007, 2008, 2009, 2011



Riverbed Technology
199 Fremont Street
San Francisco, CA 94105
Tel: +1 415 247 8800
Fax: +1 415 247 8801
www.riverbed.com

Riverbed Technology Ltd.
One Thames Valley
Wokingham Road, Level 2
Bracknell RG42 1NG
United Kingdom
Tel: +44 1344 401900

Riverbed Technology Pte. Ltd.
391A Orchard Road #22-06/10
Ngee Ann City Tower A
Singapore 238873
Tel: +65 6508-7400

Riverbed Technology K.K.
Shiba-Koen Plaza Building 9F
3-6-9, Shiba, Minato-ku
Tokyo, Japan 105-0014
Tel: +81 3 5419 1990

©2012 Riverbed Technology. All rights reserved.
Riverbed and any Riverbed product or service name or logo used herein are trademarks of Riverbed Technology. All other trademarks used herein belong to their respective owners. The trademarks and logos displayed herein may not be used without the prior written consent of Riverbed Technology or their respective owners.