











# Accessories Guide

ACCESSORIES SHIPPED IN THE BOX

Access Point Models	Mounting Brackets with Lock Arm (All Models)	Mouting Bracket with Lock Arm (XA4)	Documentation (Read Me First)	Twist Clip (15/16" with 1/2" stud for non-recessed ceiling only)	Hex Nut (1/4-20 Serr Flange, ZPS)
					
X2-120	1		1	2	2
XD2-230 / XD2-240	1		1	2	2
XD4-130 / XD4-240	1		1	4	4
XA4-240*		1	1		

XIRRUS ACCESS POINT MOUNTING GUIDE

Access Point Models	Wall Mounting Using Key Holes	Vertical Wall Mount Short Bracket	Vertical Wall Mount Long Bracket
			
X2-120	Built-in feature	XE-500-WALL	XE-4010-WALL
XD2-230 / XD2-240	Built-in feature	XE-500-WALL	XE-4010-WALL
XD4-130 / XD4-240	Built-in feature	N / A	XE-4010-WALL
XA4-240	N / A	N / A	N / A

\* Also includes PoE dongle.

SUSPENSION GRID MOUNTING OPTIONS

Access Point Models	15/16" Suspension Grid	9/16" Suspension Grid	9/16" Slotted Suspension Grid
	<p><b>CEILING TYPE</b></p>  <p>T-Bar Bracket<sup>1</sup> (with spacers)  + </p> <p>15/16" Twist Clips, 5/8" Stud<sup>2</sup> (with spacer)  + </p>	<p><b>CEILING TYPE</b></p>  <p>9/16" Twist Clips with 5/8" stud<sup>2</sup> (with spacer)  + </p>	<p><b>CEILING TYPE</b></p>  <p>T Bolt slot with 5/8" stud<sup>2</sup> (with spacer)  + </p>
	Non-Recessed	Non-Recessed	Recessed
X2-120	AP package includes (2) 15/16" Twist clips with 1/2" stud. Order XE-CLIP-KIT for replacement	Order XE-THINCLIP-KIT, which includes 1/2" bolts	Order XE-TBOLT-KIT-01
XD2-230 / XD2-240	AP package includes (2) 15/16" Twist clips with 1/2" stud. Order XE-CLIP-KIT for replacement	Order XE-THINCLIP-KIT, which includes 1/2" bolts	Order XE-TBOLT-KIT-01
XD4-130 / XD4-240	AP package includes (2) 15/16" Twist clips with 1/2" stud. Order XE-CLIP-KIT for replacement	Order XE-THINCLIP-KIT, which includes 1/2" bolts	Order XE-TBOLT-KIT-01

<sup>1</sup> For additional T BAR brackets order XE-6000-TBARX.

<sup>2</sup> All clips with 5/8" stud MUST be installed with the rubber spacers.

## ENCLOSURES AND BEAM MOUNTS

Access Point Models	Stadium Under the Seat	T-Bar Enclosure	I-Beam	Gym — Wall	GYM — I-Beam	Factory — I-Beam <sup>1</sup>	Outdoor <sup>2</sup>
							
X2-120	XE-STADIUM-OMNI	XE-6000-TBAR	XE-4000-IBEAM	XE-4000-WALL-GYM	XE-4000-IBEAM-GYM	XE-6000-IBEAM-MFG	XE-4000-OUTDOOR
XD2-230 / XD2-240	XE-STADIUM-OMNI	XE-6000-TBAR	XE-4000-IBEAM	XE-4000-WALL-GYM	XE-4000-IBEAM-GYM	XE-6000-IBEAM-MFG	XE-4000-OUTDOOR
XD4-130 / XD4-240	N / A	XE-6000-TBAR	XE-4000-IBEAM	XE-4000-WALL-GYM	XE-4000-IBEAM-GYM	XE-6000-IBEAM-MFG	XE-4000-OUTDOOR

<sup>1</sup> Order one 75W power injector.

<sup>2</sup> Order one 75W power injector to power each enclosure.

## MOUNTING KITS FOR XE-4000-OUTDOOR

Model Number	Description	Enclosure Versions
XE-6000-OUT-MNT-POLE	Pole mounting kit	XE-4000-OUTDOOR
XE-6000-OUT-MNT-CEIL	Ceiling mounting kit	XE-4000-OUTDOOR
XE-6000-OUT-MNT-WALL	Wall mounting kit	XE-4000-OUTDOOR


INJECTORS

Access Point Models	Generic PoE Switch (802.3af)	Generic PoE+ Switch (802.3at)	Generic uPoE Switch	XP1-MSI-30	XP1-MSI-75
XR-320 <sup>1</sup>	■	■	■	■	■
XH2-120 / XH2-240		■	■	■	■
X2-120	■	■	■	■	■
XD2-230 / XD2-240		■	■	■	■
XD4-130		■	■	■	■
XD4-240			■		■ <sup>2</sup>
XA4-240			■		■ <sup>2</sup>

<sup>1</sup> The XR-320 can be powered by an external 48VDC power supply that meets these specifications.

<sup>2</sup> Dongle PN310-1002-001 must be installed in-line with power/data cable to insure that legacy injectors will provide full power. Please refer to the quick install guide for more details.

Important: You must allow for loss of 4.4W between AP and switch or injector output. Cat 5e or Cat 6 cable is required; total run must be under 100 m. For more details on the installation recommendation and options, please refer to the installation manual.

Output Power	+48VDC
Nominal Load Current	0.63A
Ripple and Noise	At 20Mhz, and output parallel with 0.1uF & 10uF capacitors to ground. Temperature at 25°C, at nominal input voltage
Connector	Jack Plug 55 * 2.5 * 11.5 mm
Polarity	 <p>positive polarity</p>



Reference XR-320 External Power Supply: Mean Well GS36U48-P1J

World Headquarters  
Riverbed Xirrus  
680 Folsom St., 6th Floor  
San Francisco, CA 94107 USA  
Tel: +1 (877) 483-7233

Sunnyvale Office  
Riverbed Xirrus  
525 Almanor Ave., 5th Floor  
Sunnyvale, CA 94085 USA  
Tel: +1 (408) 664-3000

EMEA Office  
Riverbed Xirrus  
Maxis 1, 1st Floor  
Western Road, Bracknell  
Berkshire. RG12 1RT, UK  
Tel: +44 1344 401900